



FEEL THE SW
DIFFERENCE®

DESIGNED TO ENHANCE WORKER PERFORMANCE.



PF-95GW

POWDER-FREE ECOTEK SUSTAINABLE
NITRILE EXAMINATION GLOVES WITH ENERGEL
AND BREACH ALERT*

EXPERIENCE ENERGEL INFUSED GLOVES, DESIGNED TO HYDRATE SKIN AND PROTECT AGAINST LONG-TERM GLOVE USAGE

- EnerGel® Hand Conditioning Technology clinically proven to hydrate and soothe skin
- Breach Alert® Visual Detection Technology provides durable 2-ply construction and contrasting inner color
- EcoTek® Sustainable Technology*
- Proven resistance to fentanyl and gastric acid for over 4 hours to replicate hazardous settings and overdose conditions*
- Silicone-free for critical environments
- Exceeds 1.5 AQL laboratory standards

PF **PF-95GW**

WEIGHT	LENGTH	THICKNESS	FEATURES	COLOR
6.5g (large size)	9.5"	4.9 mil	EnerGel® Breach Alert® EcoTek®	GREEN WHITE


ECOTEK



Optimal thickness
for durability and
tactile sensitivity

Fully textured
surface for wet
and dry grip

Tear-resistant
beaded cuff for
easy donning



Find it at fishersci.com and fishersci.ca

fisher scientific
part of Thermo Fisher Scientific

TECHNICAL DATA



PF-95GW

POWDER-FREE ECOTEK SUSTAINABLE
NITRILE EXAMINATION GLOVES WITH ENERGEL
AND BREACH ALERT*

PRODUCT DESCRIPTION

SPECIFICATIONS

PRODUCT		PowerForm®	
GRADE		Powder-Free Exam	
MATERIAL		Nitrile	
THICKNESS	FINGER	5.9mil	0.15mm
	PALM	4.9mil	0.13mm
	CUFF	3.8mil	0.10mm
COLOR	OUTER	Green	
	INNER	White	
SURFACE	OUTER	Fully Textured	
	INNER	EnerGel®	
LENGTH		9.5"	242mm
WEIGHT		6.5g	
FIT TYPE		Ambidextrous	
CUFF TYPE		Beaded	
WATERTIGHT AQL		1.5	
ORIGIN COUNTRY		China/Malaysia	

Specifications based on size Large glove

PHYSICAL PROPERTIES

	PRE-AGING	POST-AGING
TENSILE STRENGTH:	18 MPa	18 MPa
ELONGATION:	550%	500%

INTEGRATED TECHNOLOGIES

ENERGEL Hand Conditioning Technology: allows for thorough penetration of Aloe Vera into the skin, reduces water loss to retain moisture and has been clinically proven to prevent many skin ailments, like dermatitis.

ECOTEK Sustainable Technology: Product has been tested per ASTM D5526*

BREACH ALERT Visual Detection Technology: provides durable 2-ply construction and contrasting inner color



STANDARDS & CERTIFICATIONS

EN ISO 21420:2020
EN 455-2000-2015
ASTM D6319-19
ASTM D6978-05 (2019)
ASTM F1671-13
ASTM F739-12
Reach EU 1907/2006

EU 2016/425
CAT III Complex Design
UL NFPA 1999-2018
FDA 21 CFR 177.2600

CE 0493



Please visit [swsafety.com/symbols](https://www.swsafety.com/symbols) for information on standards used on this document.

ORDERING

CAT NO.	MFG NO.	SIZE	PALM WIDTH	PACKAGING
17441029	N189471	XS 5½ – 6	2.7" 70mm	50 gloves per box 10 boxes per case
17441030	N189472	S 6½ – 7	3.1" 79mm	50 gloves per box 10 boxes per case
17441031	N189473	M 7½ – 8	3.5" 89mm	50 gloves per box 10 boxes per case
17441032	N189474	L 8½ – 9	4.1" 104mm	50 gloves per box 10 boxes per case
17441033	N189475	XL 9½ – 10	4.5" 114mm	50 gloves per box 10 boxes per case
17441034	N189476	2XL 10½ – 11	4.9" 124mm	50 gloves per box 10 boxes per case

* EcoTek gloves tested to ASTM D5526-12 Standard Test Method for Determining Anaerobic Biodegradation of Plastic Materials Under Accelerated Landfill Conditions. Results are 92.6% biodegradation in 60% solids landfill at 945 days. Future results cannot be predicted/extrapolated. If you need more information on the test reports, send email to cs@swsglobal.com.

APPLICATIONS

Chemical Handling
First Responder EMS
Clinical
Laboratory
Liquid Handling
Pharma Production

Keep out of sunlight. Store in a cool, dry place.
Keep away from sources of ozone or ignition.



R_N18947X0923

Distributed by Fisher Scientific. Contact us today:

In the United States
Order online: fishersci.com
Call customer service: 1-800-766-7000

In Canada
Order online: fishersci.ca
Call customer service: 1-800-234-7437



© 2024 Thermo Fisher Scientific Inc. All rights reserved. BN247866667-NA
Trademarks used are owned as indicated at fishersci.com/trademarks.